
















Doppel LED Navigationslichter S64 (Base) für Schiffe über 50 m



Typ (Artikelnr.)		Gewicht (g)	Energieverbrauch (W)	Tragweite (sm)	Durchmesser / Höhe (mm)	Spannung (V DC)
Backbord (130.61)		480	1,9	3	64 / 65	24
Steuerbord (131.62)		480	2,0	3	64 / 65	24
Hecklicht (132.60)		480	1,7	3	64 / 65	24
Hecklicht gelb (132.63)		480	2,1	3	64 / 65	24
Topplicht 6 sm (134.60)		550	9,8	6	64 / 81	24
Signallicht weiß (135.60)		450	2,9	3	64 / 65	24
Signallicht rot (135.61)		450	3,3	3	64 / 65	24
Signallicht grün (135.62)		450	3,1	3	64 / 65	24
Signallicht gelb (135.63)		450	2,9	3	64 / 65	24
Signallicht weiß 180° (135.60-180)		520	2,4	3	64 / 65	24
Signallicht rot 180° (135.61-180)		520	2,8	3	64 / 65	24
Signallicht grün, 180° (135.62-180)		520	2,7	3	64 / 65	24
Signallicht gelb 180° (135.63-180)		520	2,4	3	64 / 65	24

Lichtquelle	High Power LED
Betriebstemperatur	-50 °C to 55 °C
Lagertemperatur	-50 °C to 80 °C
Lebensdauer	> 100.000 h
Wartung	wartungsfrei
Anschluss	vieradrig 1 mm ² , ca. 1,5 m
Gehäuse	Aluminium, eloxiert Borosilikatglas Edelstahl V4A
Schutzart	IP 67 / 68
Zulassung	 0098