

















LED Navigationslichter S64 (Standard) für Schiffe über 50 m



Typ (Artikelnr.)		Gewicht (g)	Energieverbrauch (W)	Tragweite (sm)	Durchmesser / Höhe (mm)	Spannung (V DC)
Backbord (100.31)		330	1,9	3	64 / 54	24
Steuerbord (101.32)		330	2,0	3	64 / 54	24
Hecklicht (102.30)		330	1,7	3	64 / 54	24
Hecklicht gelb (102.33)		330	2,1	3	64 / 54	24
Topplight 6 sm (104.30)		400	9,8	6	64 / 70	24
Signallicht weiß (105.30)		300	2,9	3	64 / 54	24
Signallicht rot (105.31)		300	3,3	3	64 / 54	24
Signallicht grün (105.32)		300	3,1	3	64 / 54	24
Signallicht gelb (105.33)		300	2,9	3	64 / 54	24
Signallicht weiß 180° (105.30-180)		370	2,4	3	64 / 54	24
Signallicht rot 180° (105.31-180)		370	2,8	3	64 / 54	24
Signallicht grün 180° (105.32-180)		370	2,7	3	64 / 54	24
Signallicht grlb180° (105.33-180)		370	2,4	3	64 / 54	24
Ankermanöver (105.50)		300	4,5	5	64 / 54	24
Blitzlicht weiß (105.20)		300	2,9	3	64 / 54	24

Lichtquelle	High Power LED
Betriebstemperatur	-50 °C to 55 °C
Lagertemperatur	-50 °C to 80 °C
Lebensdauer	> 100.000 h
Wartung	wartungsfrei
Anschluss	zweiadrig 1 mm ² , ca. 1,5 m
Gehäuse	Aluminium, eloxiert Borosilikatglas Edelstahl V4A
Schutzart	IP 67 / 68
Zulassung	 0098