

















LED Navigationslichter S64 (Classic) für Schiffe über 50 m



Typ (Artikelnr.)		Gewicht (g)	Energieverbrauch (W)	Tragweite (sm)	Durchmesser / Höhe (mm)	Spannung (V DC)
Backbord (150.31)		540	1,9	3	64 / 54	24
Steuerbord (151.32)		540	2,0	3	64 / 54	24
Hecklicht (152.30)		540	1,7	3	64 / 54	24
Hecklicht gelb (152.33)		540	2,1	3	64 / 54	24
Topplicht 6 sm (154.30)		890	9,8	6	64 / 70	24
Signallicht weiß (155.30)		510	2,9	3	64 / 54	24
Signallicht rot (155.31)		510	3,3	3	64 / 54	24
Signallicht grün (155.32)		510	3,1	3	64 / 54	24
Signallicht gelb (155.33)		510	2,9	3	64 / 54	24
Signallicht weiß 180° (155.30-180)		580	2,4	3	64 / 54	24
Signallicht rot 180° (155.31-180)		580	2,8	3	64 / 54	24
Signallicht grün 180° (155.32-180)		580	2,7	3	64 / 54	24
Signallicht grlb180° (155.33-180)		580	2,4	3	64 / 54	24
Ankermanöver (155.50)		510	4,5	5	64 / 54	24
Blitzlicht weiß (155.20)		510	2,9	3	64 / 54	24

Lichtquelle	High Power LED
Betriebstemperatur	-50 °C to 55 °C
Lagertemperatur	-50 °C to 80 °C
Lebensdauer	> 100.000 h
Wartung	wartungsfrei
Anschluss	zweiadrig 1 mm ² , ca. 1,5 m
Gehäuse	Bronze CW307G Borosilikatglas Edelstahl V4A
Schutzart	IP 67 / 68
Zulassung	 0098