



















# LED Navigationslichter S64 (Base Bronze) für Schiffe bis 50 m



Type (Artikelnr.)		Gewicht (g)	Energieverbrauch (W)	Tragweite (sm)	Durchmesser / Höhe (mm)	Spannungen (V DC)
<b>Backbord (180.01)</b>		940	0,8	2	64 / 54	12 / 24
<b>Steuerbord (181.02)</b>		940	0,7	2	64 / 54	12 / 24
<b>Hecklicht (182.00)</b>		940	0,7	2	64 / 54	12 / 24
<b>Hecklicht gelb (182.03)</b>		940	0,7	2	64 / 54	12 / 24
<b>Topplight 3 nm (183.00)*</b>		920	1,8	3	64 / 54	12 / 24
<b>Topplight 5 nm (184.00)</b>		920	5	5	64 / 54	24
<b>Signallicht weiß (185.00)</b>		910	1	2	64 / 54	12 / 24
<b>Signallicht rot (185.01)</b>		910	1,1	2	64 / 54	12 / 24
<b>Signallicht grün (185.02)</b>		910	1	2	64 / 54	12 / 24
<b>Signallicht gelb (185.03)</b>		910	1	2	64 / 54	12 / 24
<b>Signallicht weiß 180° (185.00-180)</b>		980	0,9	2	64 / 54	12 / 24
<b>Signallicht rot 180° (185.01-180)</b>		980	1	2	64 / 54	12 / 24
<b>Signallicht grün 180° (185.02-180)</b>		980	0,9	2	64 / 54	12 / 24
<b>Signallicht gelb 180° (185.03-180)</b>		980	0,9	2	64 / 54	12 / 24
<b>Zweifarbent (186.08)*</b>		940	1,2	2	64 / 54	12 / 24
<b>Seglerlaterne (187.08)*</b>		940	1,6	2	64 / 54	12 / 24
<b>Seglerlaterne mit Ankerlicht (188.08) *</b>		940	1,6/1,2	2	64 / 54	12 / 24

\*für Schiffe bis 20 m

Lichtquelle	High Power LED
Betriebstemperatur	-50 °C to 55 °C
Lagertemperatur	-50 °C to 80 °C
Lebensdauer	> 100.000 h
Wartung	wartungsfrei
Anschluss	zweiadrig 1 mm <sup>2</sup> , ca. 1,5 m
Gehäuse	Bronze CW307G Borosilikatglas Edelstahl V4A
Schutzart	IP 67 / 68
Zulassung	 0098